

SHARK 282, manual pull down band sawing machine to cut from -45° to +60°.

FEATURES:

- Hydraulic transducer to visualize band saw blade tensioning.

- Wire chip brush for band saw blade cleaning.
- Double head return spring.

- Structure in grey cast iron g25, reducing drastically vibrations, grant a better stability and longer blade life.

Manual sliding vice sideways when machine mitre left or right. Fast material approach device.
Wide working surface with rotating table installed on a roller bearing, dia. 265 mm, preloaded with thrust bearing.

- Adjustable precision stops for cuts at -45°,0°, +45° and +60°.

C(CS

AIR

♀ 🛄 OIL

- Steel base with removable coolant tray.
 Electric pump for band lubrication and cooling.
 Machine arranged for handling withforklift.
 Adjustable measuring stop device to make cuts of the same length displayed on a millimeter scale. - Stock support arm with roller predisposed to
- mount loading table.
- Bi-metal band saw blade for solids and profles. - Service keys and instructions manual for
- and anstructions maintenance and spare parts list.
 The CUT CONTROL SYSTEM (CCS) can be retrofitted on machines out in the field.



OPTIONALS FROM PAG 61 - N° 02 - 03 - 04 - 08- 09-12-20- 34- 57- 72 - 80

	■ 3~		LTi	+ 0°	250	220	280x220	-
				+ 45°	230	200	220x200	
mm	kW	m/min	mm	+ 60°	120	80	140x80	kg
2950x27x0,9	1,5/1,8	36/72	285	- 45°	200	170	200x140	440

SHARK 282

SHARK 282/282CCS

